JADE 2.8/16 C-R

This C-Mount lens with 19.3 mm image circle and 400-1000 nm broadband AR coating is designed for 24.5 M / 2.74 µm pixel Sony's 4th Gen Pregius S™ technology and similar sensors. The anti-shading design prevents shading caused by micro lenses and results in a very even light distribution. A robust metal housing ensures a stable image position even under harsh environmental conditions. A special ruggedization further increases the mechanical stability of the lens.

Pregius and Pregius S are trademarks of Sony Corporation

Key features

- 1.2″ C-Mount compact lens
- For pixel size down to 2.4 µm
- Ruggedized mechanics
- For visible and near IR illumination

Applications

- Security and defense
- Space and avionics
- Traffic
- Robotics vision

Technical specifications

Type [standard]	C-R
ID [standard]	1111210
Interface	C-Mount
Focal length [mm]	16
F/# range	F/2.8 ... F/22
Numerical aperture [object | image]	- | 0.18
Max. sensor size [mm]	19.3
Max. angle of view [°]	63
Rec. magnification range	-0.1 ... 0
Rec. working distance range [mm]	150 ... ∞
Min. working distance without extension tubes [mm]	33
Filter thread [mm]	M37 x 0.75
Storage temperature [°C]	-25 … +70
Net. weight [g]	154
Additional info	Max. chief ray angle in image space = 8.6°
f'eff [mm]	16.50
SF [mm]	7.63
S'F' [mm]	16.93
HH' [mm]	25.75
ß'P	3.70
SEP [mm]	12.07
S'AP [mm]	-44.41
Σd [mm]	49.46

© Jos. Schneider Optische Werke GmbH | 3/2026 | Jos. Schneider Optische Werke GmbH is certified ISO 9001.
We accept no responsibility for any errors and reserve the right of modification without further notice.

JADE 2.8/16 C-R

MTF charts

Spectrum name	VIS					
Wavelengths [nm]	425	475	525	575	625	675
Rel. weights [%]	8	16	23	22	19	13



© Jos. Schneider Optische Werke GmbH | 3/2026 | Jos. Schneider Optische Werke GmbH is certified ISO 9001.
We accept no responsibility for any errors and reserve the right of modification without further notice.

Rel. illumination vs. image height



Distortion vs. image height



Transmittance vs. wavelength



© Jos. Schneider Optische Werke GmbH | 3/2026 | Jos. Schneider Optische Werke GmbH is certified ISO 9001.
We accept no responsibility for any errors and reserve the right of modification without further notice.

Technical drawings



© Jos. Schneider Optische Werke GmbH | 3/2026 | Jos. Schneider Optische Werke GmbH is certified ISO 9001.
We accept no responsibility for any errors and reserve the right of modification without further notice.

Accessories	Mount	Eff. length	ID
Adapter	CS-Mount	5 mm	25081
	C-Mount / M42 x 1	5.5 mm	1075817
Extension tube	C-Mount / C-Mount	5 mm	39316
	C-Mount / C-Mount	8 mm	39315
	C-Mount / C-Mount	10 mm	39312

© Jos. Schneider Optische Werke GmbH | 3/2026 | Jos. Schneider Optische Werke GmbH is certified ISO 9001.
We accept no responsibility for any errors and reserve the right of modification without further notice.

Annotation	
Focal length	Nominal focal length
F/# range	Image space F-number range for infinity focus position
Numerical aperture	Maximum real numerical aperture (depending on recommended magnification range either for infinity or respective fixed magnification)
Max. sensor size	Image circle diameter
Max. angle of view	Angle of view associated with maximum sensor size (depending on recommended magnification range either for infinity or respective fixed magnification)
Rec. magnification range	Magnification range as recommended by Schneider-Kreuznach
Rec. working distance range	Working distance, i.e. distance between object and first mechanical element, associated with recommended magnification range
Max. mechanical focus travel	Maximum possible movement of the lens from infinity position (depending on recommended magnification range either for infinity or respective fixed magnification)
Net weight	weight of unpacked lens without lens cap
f'eff	Effective focal length
SF	Distance between vertex of first lens surface and object space focal point
S'F'	Distance between vertex of last lens surface and image space focal point (back focal distance at infinity)
HH'	Distance between principal planes
ß'P	Pupil magnification (= exit pupil diameter / entrance pupil diameter)
SEP	Distance between vertex of first lens surface and entrance pupil
S'AP	Distance between vertex of last lens surface and exit pupil
Σ d	Distance between vertices of first and last lens surface
s'A	Flange focal distance (in air) for infinite object distance (depending on recommended magnification range either for infinity or respective fixed magnification)
ß'	Magnification (= image size / object size), negative value because image is inverted
OO'	Distance between object and image

Unless otherwise stated all dimensions in this data sheet are in mm.

© Jos. Schneider Optische Werke GmbH | 3/2026 | Jos. Schneider Optische Werke GmbH is certified ISO 9001.
We accept no responsibility for any errors and reserve the right of modification without further notice.

Headquarters Europe

Jos. Schneider Optische Werke GmbH

Ringstraße 132

55543 Bad Kreuznach

✆ +49 671 601 205

✉ cs@schneiderkreuznach.com

www.schneiderkreuznach.com

Offices Worldwide

America

✆ +1 800 645 7239 (East Coast)

✆ +1 800 228 1254 (West Coast)

✉ info@schneideroptics.com

Asia

✆ +86 755 8832 1170

✉ info@schneider-asiapacific.com

© Jos. Schneider Optische Werke GmbH | 3/2026 | Jos. Schneider Optische Werke GmbH is certified ISO 9001.
We accept no responsibility for any errors and reserve the right of modification without further notice.